



# PREMIER

## HIGH SECURITY SAFES



for the security conscious



# CMI SAFE CO.

Head Office: 244 West Street Carlton NSW 2218

Telephone: (02) 9547 1488 Fax: (02) 9547 2104

Website: <http://www.cmisafe.com.au> Email: [sales@cmisafe.com.au](mailto:sales@cmisafe.com.au)

**ALL CMI SAFES COME WITH A FIVE YEAR WARRANTY, EXCLUDING FREIGHT AND TRAVELLING, WITH A 12 MONTH WARRANTY ON LOCKS.**

**CMI PREMIER T.D.R.:** The design of the safes and materials used provide defence barriers resisting to:

- **Oxy-Acetylene attack**
- **Drills and abrasive grinders**
- **Explosives and force**
- **Pneumatic and hydraulic tools**


**BODY:** The body gives a minimum thickness of 80mm of high density refractory materials at all points. These materials are bonded between inner and outer walls of specially reinforced steel, becoming a complete monolith after pouring. The engagement of the door and body effectively result in a continuous cube of exceptional strength and security.

**DOOR:** The door of the Premier safe has an overall thickness of 135mm, and the 55mm thick defensive slab section contains metals highly resistant to drills and abrasive grinders in addition to the high-strength poured barrier materials and other defences. The lockcase forms an integral part of the entire door structure, giving additional strength.

**BOLTWORK:** Heavy 32mm bolts provide 4 way locking into reinforced sections of the 2 sides, top and bottom of the safe body.

**INSURANCE COVER:** Insurance surveyors have suggested **\$45,000** as a realistic rating of overnight holding of cash and valuables in an unsupported situation.

**OPTIONAL:** 115mm high lockable roll-out drawer can be provided to secure in the bottom of Premier safes at additional



**MODEL PR3**

**ANCHORING:** 2 x 20mm recessed holes are provided in all models for anchor mounting to floor.

**LOCKING:** One La-Gard 6 digit electronic combination lock which secures the heavy duty 4 way locking 32mm bolt work, further supported by two automatic glass relockers. Powered by 1 x 9v alkaline battery.

A high quality key lock can be fitted as an optional extra if required at an additional cost.

**FINISH:** CMI Premier safes are available in attractive enamel hammertone durable finishes to suit any office decor. Satin finish handles, locks and fascia panels complement the high quality appearance.

**INTERNAL FITTINGS:** All models come standard with two adjustable shelves.

**FIRE RESISTANCE**  
The Premier safe has been designed to be fire resisting for one hour

| MODEL       | CODE                 | HEIGHT             | WIDTH            | DEPTH            | WEIGHT kg   | LITRES     | LOCKING POINTS | PRICE |
|-------------|----------------------|--------------------|------------------|------------------|-------------|------------|----------------|-------|
| <b>PR1</b>  | External<br>Internal | 660 mm<br>508 mm   | 560 mm<br>405 mm | 560 mm<br>330 mm | <b>372</b>  | <b>68</b>  | <b>8</b>       | \$    |
| <b>PR2</b>  | External<br>Internal | 770 mm<br>615 mm   | 615 mm<br>457 mm | 660 mm<br>435 mm | <b>500</b>  | <b>122</b> | <b>8</b>       | \$    |
| <b>PR3</b>  | External<br>Internal | 920 mm<br>762 mm   | 615 mm<br>457 mm | 660 mm<br>435 mm | <b>568</b>  | <b>152</b> | <b>8</b>       | \$    |
| <b>PR4</b>  | External<br>Internal | 1075 mm<br>910 mm  | 660 mm<br>510 mm | 660 mm<br>435 mm | <b>704</b>  | <b>202</b> | <b>10</b>      | \$    |
| <b>PR5</b>  | External<br>Internal | 1075 mm<br>910 mm  | 765 mm<br>610 mm | 850 mm<br>585 mm | <b>926</b>  | <b>327</b> | <b>10</b>      | \$    |
| <b>PR6</b>  | External<br>Internal | 1225 mm<br>1066 mm | 765 mm<br>610 mm | 850 mm<br>585 mm | <b>1026</b> | <b>381</b> | <b>10</b>      | \$    |
| <b>PR7</b>  | External<br>Internal | 1375 mm<br>1220 mm | 765 mm<br>610 mm | 850 mm<br>585 mm | <b>1128</b> | <b>435</b> | <b>12</b>      | \$    |
| <b>PR8</b>  | External<br>Internal | 1525 mm<br>1370 mm | 765 mm<br>610 mm | 850 mm<br>585 mm | <b>1230</b> | <b>489</b> | <b>12</b>      | \$    |
| <b>PR9</b>  | External<br>Internal | 1675 mm<br>1520 mm | 765 mm<br>610 mm | 850 mm<br>585 mm | <b>1345</b> | <b>542</b> | <b>12</b>      | \$    |
| <b>PR10</b> | External<br>Internal | 1825 mm<br>1675 mm | 765 mm<br>610 mm | 850 mm<br>585 mm | <b>1464</b> | <b>595</b> | <b>12</b>      | \$    |

(IMPORTANT: PLEASE ALLOW 55MM PROJECTION FOR DOOR FURNITURE ON DEPTH MEASUREMENT)

CMI Safe Co. reserve the right to alter specifications without notice or obligation.

To deliver and install level access metro

AVAILABLE FROM



CD BBF KB 16/11/05

**MADE IN AUSTRALIA**